


- A: MATERIAL:
 1. HOUSING: PBT+30%GF UL 94V-0
 2. TERMINAL: COPPER ALLOY

- B: CHARACTERISTICS:
 1. RATING: 2.5A/250V AC
 2. INSULATION RESISTANCE: OVER 100MΩ 500VAC
 DIELECTRIC STRENGTH: 2000V AC 1 MINUTE

C: APPROVALS:
 UL, CSA, VDE, DEMKO, SEMKO, SEV & NEMKO CCC



ITEM	PART NO.	PART NAME	QTY	SPECIFICATION	MATERIAL	REMARKS
2	T-20S	TERMINAL	1 SET	SOLDER TYPE	BRASS	TIN-PLATED
1	H-20F	HOUSING	1 pcs	UL94V-0	PBT+30 %GF	

SHEN ZHEN STEADY ELECTRONICS CORPORATION
 深圳市仁达电子有限公司

PART NO.: 2120-FS1-G		NAME: AC INLET 2P	
MATERIAL: SEE ABOVE		SPEC.: 带极性	
TOLERANCE UNLESS OTHERWISE MARKED DIMENSION: 0 ~ 6 : ±0.1 6 ~ 30 : ±0.2 30 ~ 120 : ±0.3		APPROVED	
ANGULAR ±0.5		CHECKED	
UNITS: mm SCALE: 1:1 SHEET: 1 OF 1		DRAW BY 侯锡强	
		NOTE:	

REV	DATE	MODIFY

JOB NO.: 07/11/28	
-----------------------------	--