



A: MATERIAL:
 1. HOUSING: PBT+30%GF FLAMMABILITY UL 94V-0
 2. TERMINAL: COPPER ALLOY

B: CHARACTERISTICS:
 1. RATING: 10A250V AC
 2. INSULATION RESISTANCE: OVER 100M Ω 500V DC
 3. DIELECTRIC STRENGTH: 2000V AC ONE MINUTE

C: APPROVALS:
 UL, CSA, VDE, DEMKO, SEMKO, SEV, FIMKO, NEMKO & CCC

D: ORDERING OPTIONS:

ORDER#	ORDER#	TERMINAL
2108-CQF-G	1+2	4.8 SOLDER (Q.D. TABS

2	T-08Q	TERMINAL	3PCS	4.8W×0.8t	COPPER ALLOY	TIN-PLATED
1	H-08-C-G	HOUSING	1PCS	SCREW-IN TYPE	PBT+30%GF	THERMOPLASTIC
ITEM	PART NO.	PART NAME	QTY	SPECIFICATION	MATERIAL	REMARKS

深圳市仁达电子有限公司
 SHEN ZHEN STEADY ELECTRONICS CORPORATION

TOLERANCE UNLESS OTHERWISE MARKED
 DIMENSION: ANGULAR ±0.5
 0~6 : ±0.1
 6~30 : ±0.2
 30~120 : ±0.3

A		UNIT: mm	SCALE 1:1	SHEET 1 OF 1	APPROVED	CHECKED	DRAW BY 侯锡强	JOB NO.:
4							08/02/22	

A.0	2008.02.22	RE DRAWING	侯锡强	APPD.
REV	DATE	DESCRIPTION	WRITE	