



- A:MATERIAL:
 1. HOUSING: PBT WITH 30% GF UL 94V-2
 2. TERMINAL: COPPER ALLOY

- B:CHARACTERISTICS:
 1. RATING:10A250V AC EUROPE
 15A250V AC NORTH AMERICA
 2. INSULATION RESISTANCE:OVER 100MΩ 500V DC
 DIELECTRIC STRENGTH:2000V AC 0.5mA, 1 MINUTE

C:APPROVALS:
 UL, CSA, VDE, DEMKO, SEMKO, SEV, FIMKO& NEMKO CCC
 D:ORDERING OPTIONS:

ORDER#	ITEM REQ.	TERMINAL
2107-CSJ-G	① + ②	SOLDER TABS

3	T-07LBI-N	TERMINAL	2PCS		COPPER ALLOY	NI-PLATED
2	T-07LA3	TERMINAL	1PCS		COPPER ALLOY	NI-PLATED
1		HOUSING	6.8g	SNAP-IN TYPE	PBT-30%GF	THERMOPLASTIC
ITEM	PART NO.	PART NAME	QTY	SPECIFICATION	MATERIAL	REMARKS

深圳市仁达电子有限公司
 SHEN ZHEN STEADY ELECTRONICS CORPORATION

PART NO.: 2107-CSJ-G
 NAME: SCREW-MOUNT AC INLET

TOLERANCE UNLESS OTHERWISE MARKED
 DIMENSION: ANGULAR ±0.5
 0~6 : ±0.1
 6~30 : ±0.2
 30~120: ±0.3

MATERIAL: SEE ABOVE
 SPEC: _____

A.0	2008.02.22	RE DRAWING	侯锡强	
REV	DATE	DESCRIPTION	WRITE	APPD.
4				



UNIT: mm
 SCALE 1:1
 SHEET 1 OF 1

APPROVED: _____
 CHECKED: _____
 DRAW BY: 侯锡强
 JOB NO.: 08/02/22