



- A: MATERIAL:  
 1. HOUSING: NYLON FLAMMABILITY UL 94V-2  
 (94V-0 ON REQUEST)  
 2. TERMINAL: COPPER ALLOY

- B: CHARACTERISTICS:  
 1. RATING: 15A125V AC  
 2. INSULATION RESISTANCE: OVER 100M Ω 500V DC  
 3. DIELECTRIC STRENGTH: 2000V AC ONE MINUTE

ITEM	PART NO.	PART NAME	QTY	SPECIFICATION	MATERIAL	REMARKS
2	T-29-W	TERMINAL	3SET	Ø6.4*0.8t	COPPER ALLOY	TIN-PLATED
1	H-29-P	HOUSING	1	PUSHIN TYPE	NYLON/PA66	

**深圳市仁达电子有限公司**  
 SHEN ZHEN STEADY ELECTRONICS CORPORATION

TOLERANCE UNLESS OTHERWISE MARKED  
 DIMENSION:  
 0 ~ 6 : ±0.1  
 6 ~ 30 : ±0.3  
 30 ~ 120 : ±0.5

ANGULAR  
 ±0.5

PART NO.: 2129-PW-G  
 NAME: AC INLET 3P

MATERIAL: SEE ABOVE  
 SPEC.: —

APPROVED CHECKED

DRAW BY

REV: A

UNIT: mm  
 SCALE: 1:1  
 SHEET: 1 OF 1

侯锡强  
 07.11.26

JOB NO:

