



- A: MATERIAL:**
1. HOUSING: PBT WITH 30%GLASS FIBER UL94V-0 (UL 94V-2 ON REQUEST)
  2. TERMINAL: COPPERALLOY
- B: CHARACTERISTICS:**
1. RATING: 10A250V AC EUROPE  
15A250V AC NORTH AMERICA
  2. INSULATION RESISTANCE: OVER 100MΩ 500VAC  
DIELECTRIC STRENGTH: 2000V AC 1 MINUTE
- C: APPROVALS:**
- UL, CSA, VDE, DEMKO, SEMKO, SEV, FIMKO&NEMKO, CCC, KTL
- D: ORDERING OPTIONS:**

**SKILL REQUIREMENT:**

- 1 The thermostabilization reach to the rank B (over 130° c)
- 2 Injection fillet R1.0max
- 3 Injection tolerance according to the level of IT14
- 4 Symbols of grounding: width: 0.5 height: 0.5
- 5 The level of flame retardance reach to V-0

ITEM	PART NO.	PART NAME	QTY	SPECIFICATION	MATERIAL	REMARKS
3	T-07QA	TERMINAL	1 PCS	Ø4.3*0.8t	COPPER ALLOY	TIN-PLATED
2	T-07QB	TERMINAL	2 PCS	Ø4.3*0.8t	COPPER ALLOY	TIN-PLATED
1		HOUSING		SNAP-IN TYPE	PBT+30%GF	THERMOPLASTIC

**深圳市仁达电子有限公司**  
SHEN ZHEN STEADY ELECTRONICS CORPORATION

**TOLERANCE UNLESS OTHERWISE MARKED**  
DIMENSION: ANGULAR ±0.5

0 ~ 6 : ±0.1  
6 ~ 30 : ±0.2  
30 ~ 120 : ±0.3

A	4	UNIT: mm	SCALE 1:1	SHEET 1 OF 1	APPROVED	CHECKED	DRAW BY 侯锡强	JOB NO.:
---	---	----------	-----------	--------------	----------	---------	-------------	----------

A.0	2008.02.18	NEW DRAWING	侯锡强	APPD.
REV	DATE	DESCRIPTION	WRITE	