



ORDER#	ITEM REQ.	TERMINAL DIFFERENCES
2107-CQ2-G	① + ②	4.0 SOLDER Q.D. TABLETS

- A: MATERIAL:
- HOUSING: PBT WITH 30% GLASS FIBER UL94V-0 (UL 94V-2 ON REQUEST)
  - TERMINAL: COPPER ALLOY
- B: CHARACTERISTICS:
- RATING: 10A250V AC EUROPE 15A250V AC NORTH AMERICA
  - INSULATION RESISTANCE: OVER 100MΩ 500VAC
  - DIELECTRIC STRENGTH: 2000V AC 1 MINUTE
- C: APPROVALS:
- UL, CSA, VDE, DEMKO, SEMKO, SEV, FIMKO&ENEMKO, CCC, KTL
- D: ORDERING OPTIONS:

**SKILL REQUIREMENT:**

- The thermostabilization reach to the rank B (over 130° c)
- Injection fillet Rl.0max
- Injection tolerance according to the level of IT14
- Symbols of grounding: width: 0.5 height: 0.5
- The level of flame retardance reach to V-0
- The colour of PBT with beige

T-07ORA	TERMINAL	IRCS	Q44.0Mx2.0t	COPPER ALLOY	NI-PLATED
T-07ORB	TERMINAL	2 PCS	Q44.0Mx2.0t	COPPER ALLOY	NI-PLATED
	HOUSING	10g	SN&P-IN TYPE	PBT-30MGE	THERMOSTASTIC
PART NO.	PART NAME	QTY	SPECIFICATION	MATERIAL	REMARKS

**深圳市仁达电子有限公司**  
SHEN ZHEN STEADY ELECTRONICS CORPORATION

TOLERANCE UNLESS OTHERWISE MARKED  
DIMENSION:  
0~6 : ±0.1  
6~30 : ±0.2  
30~120 : ±0.3

MATERIAL:  
SEE ABOVE

SPEC.:  
BEIGE

PART NO.:  
2107-CQ2-G

NAME:  
AC INLET 3P

APPROVED: \_\_\_\_\_ CHECKED: \_\_\_\_\_ DRAW BY: 侯锡强  
JOB NO.:

A.0	2008.07.24	RE DRAWING	侯锡强	APPR.
REV	DATE	DESCRIPTION	WRITE	

UNIT:	SCALE	SHEET
mm	1:1	1 OF 1

08/07/24