



ITEM	PART NO.	PART NAME	QTY	SPECIFICATION	MATERIAL	REMARKS
2	T-14R	TERMINAL	1 SET	Ø1,7x4L	COPPER ALLOY	TIN-PLATED
1	H-14C	HOUSING	1	PCB MOUNTING	PBT-G.F.	UL 94V-0

- A: MATERIAL:
 1. HOUSING: PBT WITH GLASS FIBER FILLER UL 94V-0
 2. TERMINAL: COPPER ALLOY
 B: CHARACTERISTICS:
 1. RATING: 10A/250V AC EUROPE/NORTH AMERICA
 15A/125V AC NORTH AMERICA
 2. INSULATION RESISTANCE, DIELECTRIC STRENGTH
 MOUNTING TORQUE STRENGTH (Ø3 SCREW)
 PER APPROVAL SHEET
 C: APPROVALS:
 UL, CSA, VDE, DEMKO, SEMKO, SEV, FIMKO & NEMKO CCC
 D: ORDERING OPTIONS:

ORDER#	TERMINAL	Dim x
2114-CR7-G	PCB MOUNTING	4.7

E: RECOMMENDED DIMENSIONS FOR MOUNTING HOLE ON CHASSIS

仁达电子
 SHENZHEN ZHEN STEADY ELECTRONICS CORPORATION

PART NO.: 2114-CR7-G
 NAME: AC INLET 3P PCB MOUNTING TYPE

MATERIAL: SEE ABOVE
 SPEC.: —

TOLERANCE UNLESS OTHERWISE MARKED
 DIMENSION: ANGULAR ±0.5
 0 ~ 6 : ±0.1
 6 ~ 30 : ±0.2
 30 ~ 120 : ±0.3

APPROVED CHECKED DRAW BY REV: C
 侯锡强 Modify UL
 mark

UNIT:	SCALE	SHEET	JOB NO.:
mm	1:1	1 OF 1	07.11.28