






THICKNESS:
 0.8~1.2t (X=20.3)
 1.3~2.0t (X=20.5)



PANEL CUT



- A: MATERIAL:
 1. HOUSING: NYLON 66 FLAMMABILITY UL 94V-0
 2. TERMINAL: COPPER ALLOY

- B: CHARACTERISTICS:
 1. RATING: 10A250V AC EUROPE
 15A250V AC NORTH AMERICA
 2. INSULATION RESISTANCE: OVER 100MΩ 500VAC
 DIELECTRIC STRENGTH: 2000V AC 1 MINUTE

- C: APPROVALS:
 UL, CSA, VDE, DEMKO, SEMKO, SEV, FIMKO & NEMKO CCC, KTL
 D: ORDERING OPTIONS:

ORDER#	ITEM REQ.	TERMINAL DIFFERENCES
2111-PN1-2G	① + ②	4.0 SOLDER TABLETS

ITEM	PART NO.	PART NAME	QTY	SPECIFICATION	MATERIAL	REMARKS
3	T-07NB	TERMINAL	2 PCS	Ø4.0x5.0 8t	COPPER ALLOY	TIN-PLATED
2	T-07NA	TERMINAL	1 PCS	Ø4.0x5.0 8t	COPPER ALLOY	TIN-PLATED
1	PA66-101L	HOUSING	5.3g	SNAP-IN TYPE	PA66	HERMORPLASTIC

深圳市仁达电子有限公司
 SHEN ZHEN STEADY ELECTRONICS CORPORATION

PART NO.: 2111-PN1-2-G
 NAME: SNAP-IN TYPE AC INLET 3P

TOLERANCE UNLESS OTHERWISE MARKED
 DIMENSION: ANGULAR ±0.5
 0~6 : ±0.1
 6~30 : ±0.2
 30~120 : ±0.3

MATERIAL: SEE ABOVE
 SPEC.: _____

REV	DATE	RE. DRAWING	DISCRIPTION	WRITE	APPR.
A.0	2008.05.15			谢莉萍	

UNIT	SCALE	SHEET	APPROVED	CHECKED	DRAW BY	JOB NO.:
mm	1:1	1 OF 1			谢莉萍	