



- A: MATERIAL:**
 1. HOUSING: NYLON 66 FLAMMABILITY UL 94V-0
 2. TERMINAL: COPPER ALLOY

- B: CHARACTERISTICS:**
 1. RATING: 10A250V AC EUROPE
 15A250V AC NORTH AMERICA
 2. INSULATION RESISTANCE: OVER 100MΩ 500VAC
 DIELECTRIC STRENGTH: 2000V AC 1 MINUTE

- C: APPROVALS:**
 UL, CSA, VDE, DEMKO, SEMKO, SEV, FIMKO & NEMKO CCC
D: ORDERING OPTIONS:

ORDER#	ITEM	REQ.	TERMINAL DIFFERENCES
2111-PQ2-G	① + ②	4.8	SOLDER/Q.D.TABS

3	T-070B	TERMINAL	2 PCS	Ø4.8x0.8t	COPPER ALLOY	TIN-PLATED
2	T-070A	TERMINAL	1 PCS	Ø4.8x0.8t	COPPER ALLOY	TIN-PLATED
1		HOUSING	4.6g	SNAP-IN TYPE	PA66	THERMOPLASTIC
ITEM	PART NO.	PART NAME	QTY	SPECIFICATION	MATERIAL	REMARKS

		深圳市仁达电子有限公司 SHEN ZHEN STEADY ELECTRONICS CORPORATION	
TOLERANCE UNLESS OTHERWISE MARKED DIMENSION: ANGULAR ±0.5 0~6 : ±0.1 6~30 : ±0.2 30~120: ±0.3		PART NO.: 2111-PQ2-G NAME: SNAP-IN TYPE AC INLET 3P	
MATERIAL: SEE ABOVE SPEC.:		APPROVED: CHECKED: DRAW BY: 谢莉萍 JOB NO.:	

REV	DATE	DESCRIPTION	WRITE	APPD.
A.0	2008.05.13	RE DRAWING	谢莉萍	

A	4		UNIT: mm	SCALE 1:1	SHEET 1 OF 1
---	---	--	----------	-----------	--------------