





THICKNESS:
0.8~1.2t (X=20.3)
1.3~2.0t (X=20.5)



PANEL CUT



- A: MATERIAL:
1. HOUSING: NYLON 66 FLAMMABILITY UL 94V-0
2. TERMINAL: COPPER ALLOY

- B: CHARACTERISTICS:
1. RATING: 10A250V AC EUROPE
15A250V AC NORTH AMERICA
2. INSULATION RESISTANCE: OVER 100MΩ 500VAC
DIELECTRIC STRENGTH: 2000V AC 1 MINUTE

- C: APPROVALS:
UL, VDE, DEMKO, SEMKO, SEV, FIMKO & NEMKO CCC, KTL
D: ORDERING OPTIONS:

ORDER#	ITEM REQ.	TERMINAL DIFFERENCES
2111-PQ1-2G	① + ②	4.8 SOLDER Q.D. TABLETS

ITEM	PART NO.	PART NAME	QTY	SPECIFICATION	MATERIAL	REMARKS
3	T-070B	TERMINAL	2 PCS	Ø4.8xw0.8t	COPPER ALLOY	TIN-PLATED
2	T-070A	TERMINAL	1 PCS	Ø4.8xw0.8t	COPPER ALLOY	TIN-PLATED
1		HOUSING	3.3g	SNAP-IN TYPE	PA66	FLAMMABILITY

	深圳市仁达电子有限公司 SHEN ZHEN STEADY ELECTRONICS CORPORATION	PART NO.: 2111-PQ1-2-G	NAME: SNAP-IN TYPE AC INLET 3P
	TOLERANCE UNLESS OTHERWISE MARKED DIMENSION: 0~6 : ±0.1 6~30 : ±0.2 30~120 : ±0.3	MATERIAL: SEE ABOVE	SPEC.:

REV	DATE	DESCRIPTION	WRITE	APPD.
A.0	2008.05.15	REV DRAWING	谢莉萍	

UNIT:	SCALE	SHEET	APPROVED	CHECKED	DRAW BY	JOB NO.:
mm	1:1	1 OF 1			谢莉萍	