



- A: MATERIAL:  
 1. HOUSING: NYLON 66 FLAMMABILITY UL 94V-0  
 2. TERMINAL: COPPER ALLOY

- B: CHARACTERISTICS:  
 1. RATING: 10A250V AC EUROPE  
           15A250V AC NORTH AMERICA  
 2. INSULATION RESISTANCE: OVER 100MΩ 500VAC  
 DIELECTRIC STRENGTH: 2000V AC 1 MINUTE

- C: APPROVALS:  
 UL, CSA, VDE, DEMKO, SEMKO, SEV, FIMKO & NEMKO CCC  
 D: ORDERING OPTIONS:

ORDER#	ITEM REQ.	TERMINAL DIFFERENCES
2111-PQ5-G	① + ②	FAST-ON/Q.D.TABS

3	T-070B	TERMINAL	2 PCS	Ø4.8mm±0.8	COPPER ALLOY	TIN-PLATED
2	T-070A	TERMINAL	1 PCS	Ø4.8mm±0.8	COPPER ALLOY	TIN-PLATED
1		HOUSING	5.3g	SNAP-IN TYPE	PBT+30%GF	HERMOPLASTIC
ITEM	PART NO.	PART NAME	QTY	SPECIFICATION	MATERIAL	REMARKS

**深圳市仁达电子有限公司**  
 SHEEN ZHEN STEADY ELECTRONICS CORPORATION

TOLERANCE UNLESS OTHERWISE MARKED  
 DIMENSION: ANGULAR ±0.5  
 0~6 : ±0.1  
 6~30 : ±0.2  
 30~120 : ±0.3

PART NO.: 2111-PQ5-G  
 NAME: SNAP-IN TYPE  
 AC INLET 3P

MATERIAL: SEE ABOVE  
 SPEC.:  
 APPROVED: \_\_\_\_\_ CHECKED: \_\_\_\_\_ DRAW BY: 谢莉萍  
 08/05/15

REV	DATE	DESCRIPTION	WRITE	APPD.
A.0	2008.05.15	RE DRAWING	谢莉萍	

UNIT:	SCALE	SHEET
mm	1:1	1 OF 1