


- A: MATERIAL:
 1. HOUSING: PBT+30%GF FLAMMABILITY UL 94V-2
 (UL 94V-0 ON REQUEST)
 2. TERMINAL: COPPER ALLOY

- B: CHARACTERISTICS:
 1. RATING: 10A250V AC EUROPE/CHINA
 15A250V AC UL/CSA
 2. INSULATION RESISTANCE: OVER 100MΩ 500V/AC
 DIELECTRIC STRENGTH: 2000V AC 1 MINUTE

C: APPROVALS:
 UL, CSA, VDE, DEMKO, SEMKO, SEV, FIMKO & NEMKO CCC, KTL
 D: ORDERING OPTIONS:

ORDER#	ITEM REQ.	TERMINAL DIFFERENCES
2111-PS-2-G	① + ②	PCB MOUNTING FOR PITCH 7.0



P. C. B. LAYOUT

5	T-11P7B1	TERMINAL	2PCS	P.C.B MOUNTING	COPPER ALLOY	TIN-PLATED
4	T-11P1A1	TERMINAL	1PCS	P.C.B MOUNTING	COPPER ALLOY	TIN-PLATED
3	T-07PB	TERMINAL	2PCS		COPPER ALLOY	TIN-PLATED
2	T-07PA	TERMINAL	1PCS		COPPER ALLOY	TIN-PLATED
1	H-11-2PS-G	HOUSING	6.1g	SNAP-IN TYPE	PBT+30%GF	THERMOPLASTIC
ITEM	PART NO.	PART NAME	QTY	SPECIFICATION	MATERIAL	REMARKS

仁达
 SHEN ZHEN STEADY ELECTRONICS CORPORATION
 深圳市仁达电子有限公司

PART NO.: 2111-PS-2-G
 NAME: AC INLET 3P WITH PCB

TOLERANCE UNLESS OTHERWISE MARKED
 DIMENSION: ANGULAR ±0.5
 0~6 : ±0.1
 6~30 : ±0.2
 30~120 : ±0.3

MATERIAL: SEE ABOVE

SPEC.: _____


REVISION

UNIT: mm

SCALE 1:1

SHEET 1 OF 1

REV	DATE	DESCRIPTION	WRITE	APPD.
A.0	2008.05.15	RE DRAWING	谢莉萍	



UNIT: mm

SCALE 1:1

SHEET 1 OF 1

APPROVED CHECKED DRAW BY 谢莉萍
 JOB NO.:

08/05/15