



A: MATERIAL:
 1. HOUSING: PBT+30%GF FLAMMABILITY UL 94V-0
 2. TERMINAL: COPPER ALLOY

B: CHARACTERISTICS:
 1. RATING: 2.5A/250V AC EUROPE/ASIA
 7A/125V AC NORTH AMERICA
 2. INSULATION RESISTANCE: OVER 100MΩ 500VDC
 DIELECTRIC STRENGTH: 2000V AC 1 MINUTE

C: APPROVALS:
 UL, CSA, VDE, DEMKO, SEMKO, SEV, FIMKO& NEMKO CCC KTL

ITEM	PART NO.	PART NAME	QTY	SPECIFICATION	MATERIAL	REMARKS
3	T-231A	TERMINAL	2PCS	Ø4.8x0.5f	COPPER ALLOY	TIN-PLATED
2	T-20-2P	TERMINAL	2PCS	Ø 2.36	COPPER ALLOY	NI-PLATED
1		HOUSING	3.5g	SNAP-IN TYPE	PBT (WHITE)	THERMOPLASTIC

SHEN ZHEN STEADY ELECTRONICS CORPORATION
 深圳市仁达电子有限公司

TOLERANCE UNLESS OTHERWISE MARKED
 DIMENSION: ANGULAR ±0.5
 0~6 : ±0.1
 6~30 : ±0.2
 30~120: ±0.3

PART NO.: 2123-PSR-WH-G
 MATERIAL: SEE ABOVE
 SPEC.: WHITE
 NAME: SNAP-IN TYPE AC INLET 2P

REV	DATE	DESCRIPTION	WRITE	APPD.
A.0	2008.06.12	NEW DRAWING	谢莉萍	

UNIT:	SCALE	SHEET	APPROVED	CHECKED	DRAW BY	JOB NO.:
mm	1:1	1 OF 1			谢莉萍	