


- A: MATERIAL:**
- HOUSING: PBT+30%GF FLAMMABILITY UL 94V-2 (UL 94V-0 ON REQUEST)
 - TERMINAL: COPPER ALLOY

- B: CHARACTERISTICS:**
- RATING: 10A250V AC EUROPE/CHINA
15A250V AC UL/CSA
 - INSULATION RESISTANCE: OVER 100MQ 500VAC
DIELECTRIC STRENGTH: 2000V AC 1 MINUTE

- C: APPROVALS:**
UL, CSA, VDE, DEMKO, SEMKO, SEV, FIMKO & NEMKO CCC
- D: ORDERING OPTIONS:**

| ORDER# | DIM X. | TEXT MARK |
|--------------|--------|-----------|
| 2111-2-P7S08 | 0.8mm | 0.8 |
| 2111-2-P7S15 | 1.5mm | 1.5 |
| 2111-2-P7S20 | 2.0mm | 2.0 |



P. C. B. LAYOUT

| ITEM | PART NO. | PART NAME | QTY | SPECIFICATION | MATERIAL | REMARKS |
|------|-----------|-----------|------|---------------|--------------|---------------|
| 5 | T-07PB | TERMINAL | 2PCS | | COPPER ALLOY | TIN-PLATED |
| 4 | T-07PA | TERMINAL | 1PCS | | COPPER ALLOY | TIN-PLATED |
| 3 | T-11SPB | TERMINAL | 2PCS | | COPPER ALLOY | TIN-PLATED |
| 2 | T-11SPA | TERMINAL | 1PCS | | COPPER ALLOY | TIN-PLATED |
| 1 | H-112PS-G | HOUSING | 6.1g | SNAP-IN TYPE | PBT+30%GF | THERMOPLASTIC |

深圳市仁达电子有限公司
SHEN ZHEN STEADY ELECTRONICS CORPORATION

PART NO.: 2111-2-P7S-G
NAME: AC INLET 3P WITH PCB

TOLERANCE UNLESS OTHERWISE MARKED
DIMENSION: ANGULAR ±0.5
0~6: ±0.1
6~30: ±0.2
30~120: ±0.3

| REV | DATE | DESCRIPTION | WRITER | APPD. |
|-----|------------|-------------|--------|-------|
| A.0 | 2008.05.26 | RF DRAWING | 谢莉萍 | |

| APPROVED | CHECKED | DRAW BY | JOB NO.: |
|----------|---------|---------|----------|
| | | 谢莉萍 | 08/05/26 |