

- A: MATERIAL:
1. HOUSING: THERMOPLASTIC (NYLON 66)
 2. TERMINAL: COPPER ALLOY

- B: CHARACTERISTICS:
1. RATING: 10A250V AC
 2. INSULATION RESISTANCE: OVER 100MΩ 500VDC
 3. DIELECTRIC STRENGTH: 2000V AC ONE MINUTE
 4. FUSE: ϕ 5x 20mm

C: APPROVALS: CCC

ITEM	PART NO.	PART NAME	QTY	SPECIFICATION	MATERIAL	REMARKS
8	T-07RQ	TERMINAL	3PCS	4.8x3.0	COPPER ALLOY	TIN-PLATED
7	T-13RT	TERMINAL	2PCS		COPPER ALLOY	NI-PLATED
6	T-12FR	TERMINAL	2PCS		COPPER ALLOY	TIN-PLATED
5	T-12FC	TERMINAL	2PCS		COPPER ALLOY	TIN-PLATED
4	T-1207PA	TERMINAL	1PCS		COPPER ALLOY	N-PLATED
3	T-1207PB	TERMINAL	2PCS		COPPER ALLOY	N-PLATED
2	H-17H-G	HOUSING	2.7g	SN-PA-IN TYPE	PA66	
1	H-07-7-CB-G	HOUSING	9.15g	SN-PA-IN TYPE	PA66	

深圳市仁达电子有限公司
SHEN ZHEN STEADY ELECTRONICS CORPORATION

TOLERANCE UNLESS OTHERWISE MARKED
DIMENSION: 0 ~ 6 : ±0.1
6 ~ 30 : ±0.2
30 ~ 120 : ±0.3


ANGULAR ±0.5

PART NO.: 2107-7-CQB-G
NAME: AC INLET 3P WITH FUSE HOLDER

MATERIAL: SEE ABOVE
SPEC: _____

APPROVED: _____ CHECKED: _____ DRAW BY: 谢莉萍 JOB NO.: _____

REV	DATE	DESCRIPTION	WRITE	APPD.
A.0	2008.05.10	RE DRAWING	谢莉萍	



UNIT:	SCALE	SHEET
mm	1:1	1 OF 1

4