



- A: MATERIAL:
1. HOUSING: PA66 UL94V-0
 2. TERMINAL: COPPER ALLOY

- B: CHARACTERISTICS:
1. RATING: 10A 250V AC
 2. INSULATION RESISTANCE: OVER 100MΩ 500VDC
 3. DIELECTRIC STRENGTH: 2000V AC ONE MINUTE
 4. FUSE: $\phi 5 \times 20$ mm

C: APPROVALS:
 CCC, UL, CSA, DEMKO, NEMKO, SEMKO, SEV, FIMKO, VDE,
 D: ORDERING OPTIONS:

ORDER #	ORDER #	TERMINAL
2111-7-P-Q-G	1+2+3	4.8 SOLDER Q.D. TABS

8	T-07RQ	TERMINAL	3PCS	0.4, 8x0.8t	COPPER ALLOY	TIN-PLATED
7	T-13R11	TERMINAL	1PCS	0.5, 0x0.5t	COPPER ALLOY	TIN-PLATED
6	T-13RT	TERMINAL	2PCS		COPPER ALLOY	TIN-PLATED
5	T-13RC1	TERMINAL	2PCS		COPPER ALLOY	NI-PLATED
4	T-1207PA	TERMINAL	1PCS		COPPER ALLOY	NI-PLATED
3	T-1207PB	TERMINAL	2PCS		COPPER ALLOY	NI-PLATED
2	H-13RH-G	FUSE HOLDER	1.8g	0.5x20mm	PA66	
1	H-1-7-P-G	HOUSING	7.5g		PA66	SEMI-MOUNTING
ITEM	PART NO.	PART NAME	QTY	SPECIFICATION	MATERIAL	REMARKS

SHEN ZHEN STEADY ELECTRONICS CORPORATION
深圳市仁达电子有限公司

TOLERANCE UNLESS OTHERWISE MARKED
 DIMENSION: ANGULAR ±0.5
 .000 : ±0.1
 .0 : ±0.5

PARTNO.: 2111-7-P-Q-G
 MATERIAL: SEE ABOVE
 SPEC.:
 NAME: AC INLET 3P WITH FUSE HOLDER

REV	DATE	DESCRIPTION	WRITE	APPD.
A.0	2008.05.15	RE DRAWING	谢莉萍	

REV	DATE	DESCRIPTION	WRITE	APPD.
A.0	2008.05.15	RE DRAWING	谢莉萍	

APPROVED	CHECKED	DRAW BY	JOB NO.:
		谢莉萍	

08/05/15