



- A: MATERIAL:
1. HOUSING: PBT WITH +30%GLASS FIBER UL 94V-0
  2. TERMINAL: COPPER ALLOY

- B: CHARACTERISTICS:
1. RATING: 12V LCD/3.5A DC
  2. INSULATION RESISTANCE: OVER 5MΩ 500V DC
  3. DIELECTRIC STRENGTH: 1000V AC ONE MINUTE

5	T-D20-RA	TERMINAL	IPCS	COPPER ALLOY	TIN-PLATED	
4	T-D20-RS	TERMINAL	IPCS	COPPER ALLOY	TIN-PLATED	
3	T-D20-P	TERMINAL	IPCS	COPPER ALLOY	NI-PLATED	
2	H-202-G	HOUSING	IPCS	PBT+30%GF	THERMOPLASTIC	
1	H-DC-G	HOUSING		PBT+30%GF	THERMOPLASTIC	
ITEM	PART NO.	PART NAME	QTY	SPECIFICATION	MATERIAL	REMARKS

**深圳市仁达电子有限公司**  
SHEN ZHEN STEADY ELECTRONICS CORPORATION

TOLERANCE UNLESS OTHERWISE MARKED  
DIMENSION: ANGULAR ±0.5  
0~6 : ±0.1  
6~30 : ±0.2  
30~120 : ±0.3

PART NO.: 2120-DC-G  
NAME: DC OUTLET  
MATERIAL: SEE ABOVE  
SPEC.: 12V/3.5A DC

A.0	2008.05.27	NEW DRAWING	侯锡强	
REV	DATE	DESCRIPTION	WRITE	APPD.
4				

UNIT: mm	SCALE 1:1	SHEET 1 OF 1
----------	-----------	--------------

APPROVED	CHECKED	DRAW BY 侯锡强	JOB NO.:
		08/05/27	