


A: MATERIAL:
 1. HOUSING: PBT WITH 30% GLASS FIBER UL 94V-0
 2. TERMINAL: COPPER ALLOY

B: CHARACTERISTICS:
 1. RATING: 10A/250V AC
 2. INSULATION RESISTANCE: OVER 100MΩ 500V DC
 DIELECTRIC STRENGTH: 2000V 0.5mA AC 1 MINUTE

C: APPROVALS:
 CCC (No.2003010204032553)



ITEM	PART NO.	PART NAME	QTY	SPECIFICATION	MATERIAL	REMARKS
3	T-11W2B	TERMINAL	2PCS	04.75x0.8	COPPER ALLOY	TIN-PLATED
2	T-11W2A	TERMINAL	1PCS	04.75x0.8	COPPER ALLOY	TIN-PLATED
1		HOUSING	10g	SNAP-IN TYPE	PBT-50MCF	THERMOPLASTIC

深圳市仁达电子有限公司
 SHEN ZHEN STEADY ELECTRONICS CORPORATION

PART NO.: 2111-PW1-8G
 NAME: AC INLET 3P

TOLERANCE UNLESS OTHERWISE MARKED
 DIMENSION: ANGULAR ± 0.5

MATERIAL: SEE ABOVE
 SPEC.: _____

0 ~ 6 : ± 0.1
 6 ~ 30 : ± 0.2
 30 ~ 120 : ± 0.3

APPROVED: _____ CHECKED: _____ DRAW BY: 谢莉萍 JOB NO.: _____

REV	DATE	DESCRIPTION	WRITE	APPD.	A	UNIT:	SCALE	SHEET	APPROVED	CHECKED	DRAW BY	JOB NO.:
A.0	2008.05.4	RF DRAWING	谢莉萍		4	mm	1:1	1 OF 1			谢莉萍	