


- A: MATERIAL:**
 1. HOUSING: PBT WITH 30% GLASS FIBER UL 94V-0
 2. TERMINAL: COPPER ALLOY
- B: CHARACTERISTICS:**
 1. RATING: 10A250V AC
 2. INSULATION RESISTANCE: OVER 100MΩ 500V DC
 DIELECTRIC STRENGTH: 2000V 0.5mA AC 1 MINUTE
- C: APPROVALS:**
 CCC (No.2003010204032553)



3	T-11WB	TERMINAL	2PCS	Ø4.75x0.5t	COPPER ALLOY	TIN-PLATED
2	T-11WA	TERMINAL	1PCS	Ø4.75x0.5t	COPPER ALLOY	TIN-PLATED
1		HOUSING	10.1g	SNAP-IN TYPE	PBT-30%GF	THERMOPLASTIC
ITEM	PART NO.	PART NAME	QTY	SPECIFICATION	MATERIAL	REMARKS

深圳市仁达电子有限公司 SHENZHEN STEADY ELECTRONICS CORPORATION		PART NO.: 2111-PW1-G		NAME: AC INLET 3P	
TOLERANCE UNLESS OTHERWISE MARKED DIMENSION: 0~6 : ±0.1 6~30 : ±0.2 30~120 : ±0.3		MATERIAL: SEE ABOVE		SPEC.: _____	
ANGULAR ±0.5		APPROVED		CHECKED	
SCALE 1:1		DRAW BY 谢莉萍		JOB NO.:	
SHEET 1 OF 1		DATE 08/05/4			

REV	DATE	DESCRIPTION	WRITE
A.0	2008.05.4	RE DRAWING	谢莉萍